

OFFICE OF STATE AID ROAD CONSTRUCTION
MISSISSIPPI DEPARTMENT OF TRANSPORTATION

DATE: May 5, 2006

SUBJECT: Concrete Bridges And Structures:

Section S-804 - CONCRETE BRIDGES AND STRUCTURES; of the MISSISSIPPI STANDARD SPECIFICATIONS FOR STATE AID ROAD AND BRIDGE CONSTRUCTION 2004 EDITION is hereby amended as follows:

901-S-804.02.1--General. Add the following materials to the list of materials in Subsection 804.02.01 on page 8-51.

Ground Granulated Blast Furnace Slag (GGBFS) S-714.06
Metakaolin 901-S-714.07.01

901-S-804.02.10--Portland Cement Concrete Mix Design. Change Note ***** of Subsection S-804.02.10 on page 8-56 as follows:

***** Class DS Concrete for drilled shafts shall have an 8 ± 1 -inch slump. In the event of free fall method of concrete placement is used, the slump shall be 6 ± 1 inch.

Delete the last paragraph of Subsection S-804.02.10 on page 8-57 and substitute the following:

Either Type A, D, F, G or mid-range chemical admixture shall be used in all classes of concrete. Any combination of water reducing admixtures shall be approved by the Engineer before their use.

901-S-804.05--Basis of Payment. Add "901" prefix to the pay items listed on page 8-108.